

5040 Vegetable-Based Micro-Emulsion

FEATURES

- Excellent Tool Life
- Long Lasting and Bio-Resistant
- Very Clean and Low Residue
- Low Hydrocarbon Content
- High-Pressure Capable with Low Foam
- Chlorine-Free Extreme Pressure Technology
- Excellent Corrosion Control
- Very Low Consumption

Approved by Messier-Bugatti-Dowty

GENERAL DESCRIPTION

5040 is a time tested and proven vegetable-based technology from Hangsterfer's Laboratories. The low hydrocarbon formula utilizes special vegetable derived ingredients to achieve outstanding results in a wide variety of applications. The unique lubricity characteristics of 5040 allow for manufacturing of ferrous to non-ferrous material including exotic to medical alloys. 5040 is a chlorine-free, vegetable-based micro-emulsion that provides excellent cleanliness and tramp oil rejection, especially for high pressure coolant systems that are over 1500 psi and for companies that run lights out. The natural translucent formula provides good workpiece visibility, very low consumption, and often reduces coolant consumption by more than 20%!

APPLICATIONS

Primary		Secondary	
Boring	Reaming	Blanking	Sawing
Cutting	Thread Cutting	Centerless Grinding	Stamping
Drilling	Turning	Creep Feed Grinding	Surface Grinding
Milling		Punching	

MATERIALS

Primary		Secondary	
Aluminum	Nickel	Brass	Magnesium
Ceramics	Powdered Metals	Bronze	Plastic
Chromium	Stainless Steel	Carbide	Precious Metals
Composites	Steel	Copper	Titanium
Molybdenum	Cast Iron		

INSTRUCTIONS

Always premix coolant before adding to the machine sump. When mixing coolant by hand it is important to always add the concentrate to the water and then agitate. For best results, a Hangsterfer's recommended proportioning unit should be used. To maintain recommended concentration, make-up should be added at one-fourth the desired concentration. Always check concentration with a Refractometer. To maintain 6%: first charge the machine at 6%, then, as needed, add make-up as much as 1.5%. Avoid adding straight water or concentrate directly to machine.

OPERATION	CONCENTRATION		
	%	Ratio Concentrate: Water	Refractometer
General Machining	4 - 10	1:25 – 1:10	1.3 – 3.3
Heavy Duty Machining	8 - 12	1:12.5 – 1:8.3	2.7 – 4.0
General Grinding	6 - 8	1:16.5 – 1:12.5	2.0 – 2.7
Heavy Duty Grinding	8 - 10	1:12.5 – 1:10	2.7 – 3.3
Stamping and Forming	6 - 12	1:16.5 – 1:8.3	2.0 – 4.0

MAINTENANCE

5040 is a bio-resistant emulsion designed to control the growth of bacteria and fungus. Regular maintenance is required for maximum performance. Concentration should be monitored regularly with a calibrated refractometer. The refractometer reading needs to be multiplied by 3.0 in order to determine the actual concentration (e.g. 2 on the Refractometer = 6%). Tramp oils should be removed from the coolant surface regularly to help reduce bacterial growth. Keep the coolant system free of cleaners, solvents, and other contaminants.

PRODUCT CHARACTERISTICS

Product: 5040		Concentration Dilution Table		
Form	Liquid	%	Ratio Concentrate: Water	Refractometer
Color	Amber	10%	1:10	3.3
Odor	Mild	9%	1:11	3.0
Specific Gravity	1.015	8%	1:12.5	2.7
Viscosity: SUS @ 100°F	28.27	7%	1:14	2.3
cSt @ 40°C	6.124	6%	1:16.5	2.0
Flash Point, COC, °F/°C	Non-Flammable	5%	1:20	1.7
Fire Point, COC, °F/°C	Non-Flammable	4%	1:25	1.3
Solubility in Water	100%	3%	1:33	1.0
pH @ 10%	9.4	2%	1:50	0.7
Chlorine	0%	1%	1:100	0.3

Refractive Index Multiplier = 3

WASTE TREATMENT

If and when it is necessary to dispose of the waste coolant, the amount of coolant waste can be greatly reduced by separating the water from the oil and various contaminants which accumulate through normal machining. You can often reduce your waste disposal by more than 80%. Hangsterfer's recommends Ultra-Filtration, Chemical Treatment or Evaporation for removal of fats, oils, greases and heavy metals prior to disposal of the water phase. After approval by your local authorities, the split water may be sewerred and waste oils removed for recycling or disposal.

SHIPPING UNITS

All Hangsterfer's products are available in pails, drums and Intermediate Bulk Containers (Totes). All products are distributed worldwide.

Date: 7 February 2014 Revised: 06 December 2018

Disclaimer: All reasonable care has been taken to ensure that the information contained in this publication is true and accurate. No warranty is expressed or implied regarding the accuracy of the data. The general description, recommended uses, application data and statements in the product literature are guidelines. Because this product may be used for a variety of applications over which Hangsterfer's Laboratories, Inc. has no control, Hangsterfer's Laboratories, Inc. assumes no liability for incidental, consequential, or direct damages of any kind, regardless of causes, including negligence. Also, seller is not liable for any loss, damage or liability resulting from the use of the product in the buyer's manufacturing processes or in combination with other substances. SDS's are available for all Hangsterfer's products and should be consulted as needed.

